

# ShowTime STS118E

outdoor subwoofer



## Preliminary/Target Specifications

SINGLE-LOUDSPEAKER PERFORMANCE	
Frequency Response (-3 dB)	38 Hz – 200 Hz
Frequency Range (-10 dB)	29 Hz – 263 Hz
Nominal Coverage Pattern	Omnidirectional below 200 Hz
Audio Performance	
Power Handling	800 W continuous, 3200 W peak
Sensitivity (SPL / 1 W @ 1 m)	96 dB
Calculated Maximum SPL @ 1 m	125 dB continuous, 131 dB peak
Recommended Crossover	80 Hz – 200 Hz, requires active crossover in DSP
Recommended High-pass Protection	35 Hz with minimum 12-dB/octave filter
Loudspeaker EQ	Not required. Bose Professional EQ presets available.
TRANSDUCERS	
Low Frequency	1 × 18.0-in (457 mm) high-excursion woofer
Nominal Impedance	8 Ω
PHYSICAL	
Enclosure Material	Exterior-grade plywood
Finish	2-part spray polyurea coating, black or white
Grille	Powder-coated perforated stainless steel, paintable
Environmental	Outdoors (IP55) or indoors
Connectors	Screw terminal, (2) Neutrik® NL4 connectors
Suspension / Mounting	(4) stainless-steel M10 attachment points (top panel) (1) pole cup for 35 mm or M20-threaded loudspeaker pole (top panel)
Product Dimensions (height × width × depth)	563 mm × 570 mm × 738 mm (22.2 in × 22.4 in × 29.1 in)
Net Weight	34.5 kg (76.1 lb)
Package Contents	(1) ShowTime STS118E, (1) input cover with hardware, (1) installation guide
PRODUCT CODES	
ShowTime STS118E, black	A01477-0100 SHOWTIME STS118E BLK SUBWOOFER
ShowTime STS118E, white	A01477-0200 SHOWTIME STS118E WHT SUBWOOFER

Specifications are subject to change. © 2026 Transom Post OpCo LLC. All rights reserved. ShowTime is a trademark of Transom Post OpCo LLC. Bose is a trademark of Bose Corporation. Neutrik is a registered trademark of Neutrik AG. All other trademarks are the property of their respective owners. 05/2026